


BOMAG

TANDEM VIBRATORY ROLLER BW 80 ADH-2

PERFORMANCE DATA



Machine type	Compaction output (m ³ /h) at recommended soil layer thicknesses		
	Gravel, sand	mixed soil	Silt, clay
BW 80 ADH-2	65-120	45-90	35-70


Machine type	Compaction output (t/h) at different asphalt layer thicknesses		
	2-4 cm	6-8 cm	10-14 cm
BW 80 ADH-2	10-30	25-45	35-70

BOMAG

Technical Data

Shipping dimensions in m3
BW 80 ADH-2

without ROPS with ROPS
2,362 3,808



Standard Equipment

- ☒ Hydrostatic travel and vibration drive
- ☒ Travel drive in series
- ☒ Hydrostatic articulated steering
- ☒ Oscillating artic. center joint
- ☒ Vibration control in travel lever
- ☒ Optionally adjustable centrifugal force
- ☒ 2 scrapers per drum
- ☒ Gravity water sprinkler system
- ☒ Adjustable operator's seat
- ☒ Plastic water tanks
- ☒ Lockable engine cover
- ☒ Control and warning indicator lights
- ☒ Automatic shutdown at low oil level
- ☒ Hour meter
- ☒ Lockable anti vandal dashboard protection
- ☒ Single point lifting device
- ☒ Emergency STOP
- ☒ Vibration cut-off, rear drum
- ☒ Corrosion and weather protected ignition switch
- ☒ Fuel level indicator

Optional Equipment

- ☐ * ROPS with safety belts
- ☐ * Seat with contact switch
- ☐ Pressure sprinkler system
- ☐ Foldable ROPS
- ☐ Edge cutter
- ☐ Double travel lever
- ☐ Brake relief device (hydr.)
- ☐ Battery disconnect switch
- ☐ Individual control, vibration front and rear
- ☐ Rotary beacon
- ☐ Back-up alarm
- ☐ Environmental awareness hydraulic lubricant(n)
- ☐ Tool kit
- ☐ Special painting

* Standard delivery with CE conformity (valid within European Union)

Dimensions in mm

	A	B	C	D	H	H2	K	L	O	S	W
BW 80 ADH-2	1282	856	458	580	1482	2300	250	1862	28	13	800

Technical Data

BOMAG
BW 80 ADH-2

Weights

Operating weight CECE	kg	1.620
Average static linear load CECE	kg/cm	10,1

Dimensions

Working width	mm	800
Length with ROPS	mm	1.934
Track radius, inner	mm	2.020

Driving Characteristics

Max. working speed with vibration	km/h	0- 4,5
Max. travel speed	km/h	0- 8,0
Max. gradeability without/with vibr.	%	40/30

Drive

Engine manufacturer	Kubota
Type	D 722 B
Cooling	water
Number of cylinders	3
Performance ISO 9249	kW 11,9
Speed	min-1 3.000
Performance SAE J 1349	kW 11,9
Performance SAE J 1349	hp 15,9
Speed	min-1 3.000
Electric equipment	V 12
Drive system	hydrost.
Driven drum	front + rear

Brakes

Service brake	hydrost.
Parking brake	hydromec.

Steering

Steering system	oscil.artic.
Steering method	hydrost.
Steering angle +/-	grad 31
Oscillating angle +/-	grad 6

Exciter system

Vibrating drum	front + rear
Drive system	hydrost.
Frequency	Hz 60/40
Amplitude	mm 0,50
Centrifugal force (each drum)	kN 15/7
Centrifugal force	t 1,5/0,7

Sprinkler System

Type of sprinkling	gravity
--------------------	---------

Capacities

Fuel	l	23
Water	l	100

Technical modifications reserved. Machines may be shown with options.



BOMAG GmbH & CO. OHG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090
Fax (0)6742 - 3090

BOMAG